



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 7/1/2020
Version: 4
Language: en-GB,IE
Date of print: 27/8/2020

Negative E-Beam Resist Series SX AR-N 8200 & 8250

Material number SX AR-N 8200 & 8250

Page: 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Negative E-Beam Resist Series SX AR-N 8200 & 8250

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Coating agent, Intermediate for electronic industry
For industrial purposes only

1.3 Details of the supplier of the safety data sheet

Company name: Allresist
Gesellschaft für chemische Produkte zur Mikrostrukturierung mbH
Street/POB-No.: Am Biotop 14
Postal Code, city: 15344 Strausberg
WWW: www.allresist.de
E-mail: info@allresist.de
Telephone: +49 (0)33 41-35 93-0
Telefax: +49 (0)33 41-35 93-29
Department responsible for information:
Frau Dr. Zimmermann, Email: produktion@allresist.de

1.4 Emergency telephone number

Telephone: +49 (0)33 41-35 93-0
Only available during office hours.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.
Eye Irrit. 2; H319 Causes serious eye irritation.
STOT SE 3; H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling (CLP)



Signal word: **Warning**

Hazard statements: H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 7/1/2020
Version: 4
Language: en-GB,IE
Date of print: 27/8/2020

Negative E-Beam Resist Series SX AR-N 8200 & 8250

Material number SX AR-N 8200 & 8250

Page: 2 of 11

Precautionary Statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided. Inhaling can lead to irritations of the respiratory tract and mucous membrane. Higher doses may lead to a narcotic effect. Special danger of slipping by leaking/spilling product.

Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition / information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Silicone-resin.

Hazardous ingredients:

Ingredient	Designation	Content	Classification
EC No. 203-539-1 CAS 107-98-2	1-Methoxy-2-propanol	>= 80 %	Flam. Liq. 3; H226. Eye Irrit. 2; H319. STOT SE 3; H336.
-	Silsesquioxane	< 20 %	Eye Irrit. 2; H319.

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General information: If medical advice is needed, have product container or label at hand. First aider: Pay attention to self-protection!
- In case of inhalation: Move victim to fresh air; if necessary, provide artificial respiration or oxygen. Seek medical treatment in case of troubles.
- Following skin contact: Remove residues with soap and water. Take off contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 7/1/2020
Version: 4
Language: en-GB,IE
Date of print: 27/8/2020

Negative E-Beam Resist Series SX AR-N 8200 & 8250

Material number SX AR-N 8200 & 8250

Page: 3 of 11

After swallowing: Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. May cause drowsiness or dizziness.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Water spray jet, foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour. With air, vapours form potentially explosive mixtures, which are heavier than air. Vapours may proceed on the ground over great distances and cause fire and backflashes.

On heating or in case of fire toxic gases may form.

Furthermore, there may develop: acetic acid, ethylene, carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

In case of fire and/or explosion do not breathe fumes.

Additional information:

Hazchem-Code: •3Y

Heating will lead to pressure increase: Danger of bursting and explosion. Use fine water spray to cool endangered containers.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water. Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Wear appropriate protective equipment. Provide adequate ventilation. Do not breathe vapour/aerosol. Avoid contact with the substance. Take off immediately all contaminated clothing and wash it before reuse. If possible, eliminate leakage. Cordon off downwind area at risk and warn inhabitants. Keep unprotected people away.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 7/1/2020
Version: 4
Language: en-GB,IE
Date of print: 27/8/2020

Negative E-Beam Resist Series SX AR-N 8200 & 8250

Material number SX AR-N 8200 & 8250

Page: 4 of 11

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion!
In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Beware of reignition. Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information: Use explosion-proof equipment and non-sparking tools/utensils.

Special danger of slipping by leaking/spilling product.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed.

Avoid contact with skin, eyes, and clothing.

Wear appropriate protective equipment. When using do not eat, drink or smoke. Do not breathe vapour/aerosol. Take off immediately all contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation. When handling large quantities, supply emergency spray.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Use only non-sparking tools. Use explosion-proof electrical/ventilating/lighting equipment. Do not weld. In partially filled containers explosive mixtures may form.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep only in original container. Keep container dry, tightly closed and store at cool and aired place. Protect from heat and direct sunlight.

Storage temperature: 8 - 12 °C.

Hints on joint storage:

Do not store together with bases or amines.

Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 7/1/2020
Version: 4
Language: en-GB,IE
Date of print: 27/8/2020

Negative E-Beam Resist Series SX AR-N 8200 & 8250

Material number SX AR-N 8200 & 8250

Page: 5 of 11

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
107-98-2	1-Methoxy-2-propanol	Europe: IOELV: STEL	568 mg/m ³ ; 150 ppm (may be absorbed through the skin)
		Europe: IOELV: TWA	375 mg/m ³ ; 100 ppm (may be absorbed through the skin)
		Great Britain: WEL-STEL	560 mg/m ³ ; 150 ppm (may be absorbed through the skin)
		Great Britain: WEL-TWA	375 mg/m ³ ; 100 ppm (may be absorbed through the skin)
		Ireland: 15 minutes	568 mg/m ³ ; 150 ppm
		Ireland: 8 hours	375 mg/m ³ ; 100 ppm

Additional information: The product can be absorbed through skin.

8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Explosion protection required.

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded. Use filter type A (= against vapours of organic substances) according to EN 14387.

Hand protection: Protective gloves according to EN 374.
Glove material: Nitrile rubber, Neoprene.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to EN 166.

Body protection: Flame retardant, antistatic and chemical resistant protective clothing.

General protection and hygiene measures:

Avoid contact with skin, eyes, and clothing. When using do not eat, drink or smoke. Wash hands before breaks and after work. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Do not breathe vapour/aerosol. Take off immediately all contaminated clothing and wash it before reuse. When handling large quantities, supply emergency spray.

Environmental exposure controls

Do not allow to enter into ground-water, surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Physical state at 20 °C and 101.3 kPa: liquid
Colour: clear



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 7/1/2020
Version: 4
Language: en-GB,IE
Date of print: 27/8/2020

Negative E-Beam Resist Series SX AR-N 8200 & 8250

Material number SX AR-N 8200 & 8250

Page: 6 of 11

Odour:	mild
Odour threshold:	No data available
pH value:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	117 °C
Flash point/flash point range:	34 °C
Evaporation rate:	No data available
Flammability:	Flammable liquid and vapour.
Explosion limits:	LEL (Lower Explosion Limit): 1.70 Vol-% (1-Methoxy-2-propanol) UEL (Upper Explosive Limit): 13.10 Vol-% (1-Methoxy-2-propanol)
Vapour pressure:	No data available
Vapour density:	No data available
Density:	0.97 g/mL
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	-0.437 log P(o/w) (1-Methoxy-2-propanol) Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.
Auto-ignition temperature:	No data available
Decomposition temperature:	Above 180 °C
Viscosity, kinematic:	No data available
Explosive properties:	On contact with air, potentially explosive mixtures may develop.
Oxidizing characteristics:	No data available

9.2 Other information

Additional information: No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Flammable liquid and vapour.
Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Heating will lead to pressure increase: Danger of bursting and explosion.
Reacts with bases and amines.
Contact with bases liberates ethylene.

10.4 Conditions to avoid

Keep away from heat sources, sparks and open flames.
Protect from direct sunlight.

10.5 Incompatible materials

Bases, amines.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 7/1/2020
Version: 4
Language: en-GB,IE
Date of print: 27/8/2020

Negative E-Beam Resist Series SX AR-N 8200 & 8250

Material number SX AR-N 8200 & 8250

Page: 7 of 11

10.6 Hazardous decomposition products

Thermal decomposition: Ethylene, acetic acid, organic acids vapours.
Above 180 °C

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Eye Irrit. 2; H319 = Causes serious eye irritation.

Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.

Skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): STOT SE 3; H336 = May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Other information: Information about 1-Methoxy-2-propanol:
LC50 Rat, inhalative (mist): > 6 mg/L/4h

Symptoms

In case of inhalation: Irritation to respiratory tract

In case of ingestion: May be harmful if swallowed.

After contact with skin: May cause skin irritation.

After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Information about 1-Methoxy-2-propanol:
Fish toxicity:
LC50 Pimephales promelas (fathead minnow): 20.8 mg/L/96h
Daphnia toxicity:
EC50 Daphnia magna (Big water flea): 23,300 mg/L/48h



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 7/1/2020
Version: 4
Language: en-GB,IE
Date of print: 27/8/2020

Negative E-Beam Resist Series SX AR-N 8200 & 8250

Material number SX AR-N 8200 & 8250

Page: 8 of 11

12.2 Persistence and degradability

Further details: No data available

12.3 Bioaccumulative potential

Bioconcentration factor (BCF):

Information about 1-Methoxy-2-propanol:
Bioconcentration factor (BCF), fish: < 2

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 16 03 05* = organic wastes containing hazardous substances
* = Evidence for disposal must be provided.

Recommendation: Dispose of waste according to applicable legislation.
Do not dispose of with household waste.
Do not empty into drains.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.
Handle contaminated packages in the same way as the substance itself.
Handle empty containers with care. Incineration may cause explosion.
Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

ADR/RID, IMDG, IATA-DGR:

UN 1139

14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR:

UN 1139, COATING SOLUTION



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 7/1/2020
Version: 4
Language: en-GB,IE
Date of print: 27/8/2020

Negative E-Beam Resist Series SX AR-N 8200 & 8250

Material number SX AR-N 8200 & 8250

Page: 9 of 11

14.3 Transport hazard class(es)

ADR/RID: Class 3, Code: F1
IMDG: Class 3, Subrisk -
IATA-DGR: Class 3



14.4 Packing group

ADR/RID, IMDG, IATA-DGR:
III

14.5 Environmental hazards

Marine pollutant: no

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board: ADR/RID: Kemmler-number 30, UN number UN 1139
Hazard label: 3
Limited quantities: 5 L
EQ: E1
Contaminated packaging - Instructions: P001 IBC03 LP01 R001
Special provisions for packing together: MP19
Portable tanks - Instructions: T2
Portable tanks - Special provisions: TP1
Tank coding: LGBF
Tunnel restriction code: D/E

Sea transport (IMDG)

EmS: F-E, S-E
Special provisions: 955
Limited quantities: 5 L
Excepted quantities: E1
Contaminated packaging - Instructions: P001, LP01
Contaminated packaging - Provisions: -
IBC - Instructions: IBC03
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T2
Tank instructions - Provisions: TP1
Stowage and handling: Category A.
Properties and observations: Miscibility with water depends upon the composition.
Segregation group: none

Air transport (IATA)

Hazard label: Flamm. liquid
Excepted Quantity Code: E1
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y344 - Max. Net Qty/Pkg. 10 L
Passenger and Cargo Aircraft: Pack.Instr. 355 - Max. Net Qty/Pkg. 60 L
Cargo Aircraft only: Pack.Instr. 366 - Max. Net Qty/Pkg. 220 L
Special provisions: A3
Emergency Response Guide-Code (ERG): 3L



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 7/1/2020
Version: 4
Language: en-GB,IE
Date of print: 27/8/2020

Negative E-Beam Resist Series SX AR-N 8200 & 8250

Material number SX AR-N 8200 & 8250

Page: 10 of 11

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Great Britain

Hazchem-Code: •3Y
No data available

National regulations - EC member states

Volatile organic compounds (VOC):
> 80 % by weight = 776 g/L

Labelling of packaging with <= 125mL content



Signal word: **Warning**

Hazard statements: not applicable

Precautionary Statements:
not applicable

Further regulations, limitations and legal requirements:
Use restriction according to REACH annex XVII, no.: 3

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Further information

Wording of the H-phrases under paragraph 2 and 3:
H226 = Flammable liquid and vapour.
H319 = Causes serious eye irritation.
H336 = May cause drowsiness or dizziness.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 7/1/2020

Version: 4

Language: en-GB,IE

Date of print: 27/8/2020

Negative E-Beam Resist Series SX AR-N 8200 & 8250

Material number SX AR-N 8200 & 8250

Page:

11 of 11

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL: Occupational Exposure Limit Value
AS/NZS: Australian Standards/New Zealand Standards
BCF: Bioconcentration Factor
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC50: Effective Concentration 50%
EC: European Community
EN: European Standard
EU: European Union
IATA: International Air Transport Association
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
LC50: Median lethal concentration
LEL: Lower Explosion Limit
log P(o/w): Partition coefficient: octanol/water
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
STOT SE: Specific target organ toxicity - single exposure
TLV: Threshold Limit Value
TSCA: Toxic Substance Control Act
UN: United Nations
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

Reason of change: Changes in section 14: General revision

Date of first version: 30/5/2018

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.